

STP Toolbox for Matlab/Octave*

Hongsheng Qi, Daizhan Cheng

[†]Key Laboratory of Systems and Control, Chinese Academy of Sciences

[‡]Academy of Mathematics and Systems Science, Chinese Academy of Sciences, Beijing 100190, P.R.China

E-mail: qihongsh@amss.ac.cn, dcheng@iss.ac.cn

Last Updated on August 26, 2016

1 Introduction

The semi-tensor product (STP) of matrices is a novel matrix product, which is a generalization of conventional matrix product for the case when the two factor matrices even do not meet the dimension matching condition [1, 2, 3, 4, 5].

The STP toolbox for Matlab¹ and GNU Octave² is developed for calculating the semi-tensor product (STP) of (logical) matrices and its application to the analysis and control of Boolean networks.

The semi-tensor product of matrices is defined as follows

Definition 1.1 1. Let X be a row vector of dimension np , and Y be a column vector with dimension p . Then we split X into p equal-size blocks as X^1, \dots, X^p , which are $1 \times n$ rows. The (left) STP, denoted by \ltimes , is defined as

$$\begin{cases} X \ltimes Y = \sum_{i=1}^p X^i y_i \in \mathbb{R}^n, \\ Y^T \ltimes X^T = \sum_{i=1}^p y_i (X^i)^T \in \mathbb{R}^n. \end{cases} \quad (1)$$

2. Let $A \in \mathcal{M}_{m \times n}$ and $B \in \mathcal{M}_{p \times q}$. If either n is a factor of p , say $nt = p$ and denote it as $A \prec_t B$, or p is a factor of n , say $n = pt$ and denote it as $A \succ_t B$, then the (left) STP of A and B , denoted by $C = A \ltimes B$, is defined as the following: C consists of $m \times q$ blocks as $C = (C^{ij})$ and each block is

$$C^{ij} = A^i \ltimes B_j, \quad i = 1, \dots, m, \quad j = 1, \dots, q,$$

where A^i is i -th row of A and B_j is the j -th column of B .

The above definition is for the two matrices satisfying multiple dimension condition, the following definition is a general case for two arbitrary matrices.

Definition 1.2 Let $A \in \mathcal{M}_{m \times n}$ and $B \in \mathcal{M}_{p \times q}$. The (left) semi-tensor product of A and B is defined as

$$A \ltimes B = (A \otimes I_{t/n})(B \otimes I_{t/p}), \quad (2)$$

where t is the least common multiple of n and p , and \otimes is the Kronecker product.

*Supported partly by National Natural Science Foundation of China under Grants 60674022, 60736022, 60221301, and 61104065.

¹<http://www.mathworks.com>

²<http://www.octave.org>

We use some simple numerical examples to describe it.

Example 1.3 1. Let $X = \begin{bmatrix} 1 & 2 & 3 & -1 \end{bmatrix}$ and $Y = \begin{bmatrix} 1 \\ 2 \end{bmatrix}$. Then

$$X \ltimes Y = \begin{bmatrix} 1 & 2 \end{bmatrix} \cdot 1 + \begin{bmatrix} 3 & -1 \end{bmatrix} \cdot 2 = \begin{bmatrix} 7 & 0 \end{bmatrix}.$$

2. Let

$$A = \begin{bmatrix} 1 & 2 & 1 & 1 \\ 2 & 3 & 1 & 2 \\ 3 & 2 & 1 & 0 \end{bmatrix}, \quad B = \begin{bmatrix} 1 & -2 \\ 2 & -1 \end{bmatrix}.$$

Then

$$A \ltimes B = \begin{bmatrix} \begin{pmatrix} 1 & 2 & 1 & 1 \end{pmatrix} \begin{pmatrix} 1 \\ 2 \end{pmatrix} & \begin{pmatrix} 1 & 2 & 1 & 1 \end{pmatrix} \begin{pmatrix} -2 \\ -1 \end{pmatrix} \\ \begin{pmatrix} 2 & 3 & 1 & 2 \end{pmatrix} \begin{pmatrix} 1 \\ 2 \end{pmatrix} & \begin{pmatrix} 2 & 3 & 1 & 2 \end{pmatrix} \begin{pmatrix} -2 \\ -1 \end{pmatrix} \\ \begin{pmatrix} 3 & 2 & 1 & 0 \end{pmatrix} \begin{pmatrix} 1 \\ 2 \end{pmatrix} & \begin{pmatrix} 3 & 2 & 1 & 0 \end{pmatrix} \begin{pmatrix} -2 \\ -1 \end{pmatrix} \end{bmatrix} = \begin{bmatrix} 3 & 4 & -3 & -5 \\ 4 & 7 & -5 & -8 \\ 5 & 2 & -7 & -4 \end{bmatrix},$$

or

$$A \ltimes B = A(B \otimes I_2) = \begin{bmatrix} 1 & 2 & 1 & 1 \\ 2 & 3 & 1 & 2 \\ 3 & 2 & 1 & 0 \end{bmatrix} \begin{bmatrix} 1 & 0 & -2 & -0 \\ 0 & 1 & -0 & -2 \\ 2 & 0 & -1 & -0 \\ 0 & 2 & -0 & -1 \end{bmatrix} = \begin{bmatrix} 3 & 4 & -3 & -5 \\ 4 & 7 & -5 & -8 \\ 5 & 2 & -7 & -4 \end{bmatrix}.$$

□

Definition 1.4 1. An $n \times p$ matrix, A , is called a logical matrix if

$$A = [\delta_n^{i_1} \ \delta_n^{i_2} \ \cdots \ \delta_n^{i_p}], \quad (3)$$

where δ_n^i is the i -th column of the identity matrix I_n .

2. The condense form of a logical matrix (as A in (3)) is denoted as

$$A = \delta_n[i_1, i_2, \dots, i_p]. \quad (4)$$

Remark 1.5 According to (4), an $n \times p$ logical matrix is described by a vector of dimension p and a parameter n . In the toolbox `lm` object is used to express a logical matrix as

$$\begin{cases} \text{lm.n} = n, \\ \text{lm.v} = [i_1, i_2, \dots, i_p]. \end{cases} \quad (5)$$

Example 1.6 Consider

$$A = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}.$$

It is a logical matrix and it can be expressed in condensed form as

$$A = \delta_4[1, 3, 2, 4].$$

Expressing A to a `lm` object, we have

$$\begin{cases} A.n = 4, \\ A.v = [1 \ 3 \ 2 \ 4]. \end{cases}$$

In this expression we only need 5 bytes instead of 16 bytes in the memory.

□

Definition 1.7 The swap matrix $W_{[m,n]}$ is an $mn \times mn$ matrix constructed in the following way: label its columns by $(11, 12, \dots, 1n, \dots, m1, m2, \dots, mn)$ and its rows by $(11, 21, \dots, m1, \dots, 1n, 2n, \dots, mn)$. Then its element in the position $((I, J), (i, j))$ is assigned as

$$w_{(IJ),(ij)} = \delta_{i,j}^{I,J} = \begin{cases} 1, & I = i \text{ and } J = j, \\ 0, & \text{otherwise.} \end{cases} \quad (6)$$

Remark 1.8 Let $X \in \mathbb{R}^m$ and $Y \in \mathbb{R}^n$ be two columns. Then

$$W_{[m,n]} \ltimes X \ltimes Y = Y \ltimes X. \quad (7)$$

Example 1.9 Let $m = 2$ and $n = 3$, the swap matrix $W_{[2,3]}$ is constructed as

$$W_{[2,3]} = \begin{matrix} & \begin{matrix} (11) & (12) & (13) & (21) & (22) & (23) \end{matrix} \\ \begin{matrix} (11) \\ (21) \\ (12) \\ (22) \\ (13) \\ (23) \end{matrix} & \begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 \end{bmatrix} \end{matrix}.$$

In condensed form we have

$$W_{[2,3]} = \delta_6[1, 3, 5, 2, 4, 6].$$

□

Definition 1.10 Let A be an $m \times n$ matrix, $m = pq$, $n = rs$. Express A in blocks as

$$A = \begin{bmatrix} A_{11} & A_{12} & \cdots & A_{1s} \\ A_{21} & A_{22} & \cdots & A_{2s} \\ \vdots & & & \\ A_{q1} & A_{q2} & \cdots & A_{qs} \end{bmatrix}, \quad (8)$$

where A_{ij} are $p \times r$ matrices. Then the block transpose $A^{T(p,r)}$ is defined as

$$A = \begin{bmatrix} A_{11} & A_{21} & \cdots & A_{q1} \\ A_{12} & A_{22} & \cdots & A_{q2} \\ \vdots & & & \\ A_{1s} & A_{2s} & \cdots & A_{qs} \end{bmatrix}. \quad (9)$$

2 Functions and Objects

This section provides detailed description for the basic functions in this toolbox. Both Matlab and Octave support the object-oriented programming, thus the toolbox defines **stp** object for the calculations of STP and **lm** object for the logical matrices.

2.1 Basic Functions

1. $C = sp(A, B)$

Description: The function performs the (left) semi-tensor product of two matrices A and B based on Definition 1.2.

Argument(s): Two matrices A and B with arbitrary dimensions.

Returned Value: $C = A \ltimes B$.

2. $C = sp1(A, B)$

Description: The function performs the (left) semi-tensor product of two matrices A and B according to Definition 1.1.

Argument(s): Two matrices A and B with arbitrary dimensions.

Returned Value: $C = A \ltimes B$.

Note that sp and $sp1$ are functionally same. Because they use different algorithms inside, $sp1$ should be faster than sp for multiple dimension condition.

3. $C = spn(A_1, A_2, \dots, A_n)$

Description: The function performs the (left) semi-tensor product of finite set of matrices A_1, \dots, A_n .

Argument(s): Finite matrices A_1, \dots, A_n which are of arbitrary dimension.

Returned Value: $C = \ltimes_{i=1}^n A_i$.

4. $B = bt(A, p, r)$

Description: The function performs the block transpose of A (refer to Definition 1.10).

Argument(s): A is the matrix to be transposed, the size of fixed blocks is $p \times r$.

Returned Value: $B = A^{T(p,r)}$.

5. $W = wij(m, n)$

Description: The function produces an $mn \times mn$ swap matrix (refer to Definition 1.7).

Argument(s): Two positive integers m and n . n is optional, default n is m .

Returned Value: Matrix W of dimension $mn \times mn$.

6. $v = vc(A)$

Description: The function converts a matrix to its column stacking form.

Argument(s): Matrix $A = (a_{ij})_{m \times n}$.

Returned Value: $v = [a_{11} \ \dots \ a_{m1} \ \dots \ a_{1n} \ \dots \ a_{mn}]^T$.

7. $v = vr(A)$

Description: The function converts a matrix to its row stacking form.

Argument(s): Matrix $A = (a_{ij})_{m \times n}$.

Returned Value: $v = [a_{11} \ \dots \ a_{1n} \ \dots \ a_{m1} \ \dots \ a_{mn}]^T$.

8. $A = invvc(x, m)$

Description: Let $x = (x_1, x_2, \dots, x_p)$. The function will reshape x into a matrix A with row number m as

$$A = \begin{bmatrix} x_1 & x_{m+1} & \dots & x_{p-m+1} \\ x_2 & x_{m+2} & \dots & x_{p-m+2} \\ \vdots & & & \\ x_m & x_{2m} & \dots & x_p \end{bmatrix}.$$

If p is not a multiple of m , the least number of zeros will be added at the end of x such that the length of x becomes a multiple of m .

Argument(s): x is a vector; m is the row number of the resulting matrix, and it is optional. Default m is $\text{ceil}(\text{sqrt}(\text{length}(x)))$.

Returned Value: Matrix A with row number m .

9. $A = \text{invvr}(x, n)$

Description: Let $x = (x_1, x_2, \dots, x_p)$. The function will reshape x into a matrix A with column number n as

$$A = \begin{bmatrix} x_1 & x_2 & \cdots & x_n \\ x_{n+1} & x_{n+2} & \cdots & x_{2n} \\ \vdots & & & \\ x_{p-n+1} & x_{p-n+2} & \cdots & x_p \end{bmatrix}.$$

If p is not a multiple of n , the least number of zeros will be added at the end of x such that the length of x becomes a multiple of n .

Argument(s): x is a vector; m is the column number of the resulting matrix, and it is optional. Default m is $\text{ceil}(\text{sqrt}(\text{length}(v)))$.

Returned Value: Matrix A with column number m .

10. $v = \text{dec2any}(a, k, \text{len})$

Description: The function converts a decimal number a into a k -based number as

$$a = a_s k^s + a_{s-1} k^{s-1} + \cdots + a_1 k + a_0, \quad a_s > 0.$$

[Say, $k = 2$, the result is a binary number in vector form. In fact the function $\text{dec2binv}(a, \text{len})$ is for binary case, which is a wrapper of this function. Note that in Matlab/Octave there is dec2base (or dec2bin) to do the same thing, but its returned value is a string.]

Argument(s): a is a positive integer; k is optional, and $k \geq 2$. Default k is 2. Default len is 0, it means $a_s \neq 0$, but if $\text{len} > 0$ and $\text{len} > s + 1$, $\text{len} - s - 1$ zeros should be added at the beginning of returned value.

Returned Value: $v = [a_s \ a_{s-1} \ \cdots \ a_1 \ a_0]$.

2.2 stp Object

Here we would like to introduce the functions for **stp** object.

1. $M = \text{stp}(A)$

Description: **stp** class constructor.

Argument(s): Matrix A .

Returned Value: **stp** object M .

Since **stp** object is a simple wrapper, more usage could be found in the examples in Section 3.

2.3 lm Object

Now we will introduce the functions for logical matrices or **lm** object.

1. $M = \text{lm}(A)$ or $M = \text{lm}(v, n)$

Description: **lm** class constructor.

Argument(s): i) Logical matrix A ; ii) vector $v = [v_1 \ v_2 \ \cdots \ v_p]$ and positive integer n satisfying $0 \leq v_i \leq n$, $1 \leq i \leq p$. (Case i, refer to Definition 1.4 and Example 1.6; Case ii, $\text{lm}.n = n$, $\text{lm}.v = v$.)

Returned Value: **lm** object M .

2. $C = lsp(A, B)$

Description: The function performs the semi-tensor product of logical matrices A and B .

Argument(s): A, B are \mathbf{lm} objects. (refer to Definition 1.4 and Remark 1.5 for the structure.)

Returned Value: $C = A \ltimes B$ is an \mathbf{lm} object.

3. $C = lspn(A_1, A_2, \dots, A_n)$

Description: The function performs the semi-tensor product of logical matrices A_1, A_2, \dots, A_n .

Argument(s): A_1, \dots, A_n are \mathbf{lm} objects. (refer to Definition 1.4 and Remark 1.5 for the structure.)

Returned Value: $C = \ltimes_{i=1}^n A_i$ is an \mathbf{lm} object.

4. $M = leye(n)$

Description: The function produces an $n \times n$ identity matrix.

Argument(s): Positive integer n .

Returned Value: \mathbf{lm} object M .

5. $M = lmn(k)$

Description: The function produces the structure matrix of negation for k -valued logic ($k \geq 2$).

Argument(s): k is optional, default k is 2.

Returned Value: \mathbf{lm} object M .

6. $M = lmc(k)$

Description: The function produces the structure matrix of conjunction for k -valued logic ($k \geq 2$).

Argument(s): k is optional, default k is 2.

Returned Value: \mathbf{lm} object M .

7. $M = lmd(k)$

Description: The function produces the structure matrix of disjunction for k -valued logic ($k \geq 2$).

Argument(s): k is optional, default k is 2.

Returned Value: \mathbf{lm} object M .

8. $M = lmi(k)$

Description: The function produces the structure matrix of implication for k -valued logic ($k \geq 2$).

Argument(s): k is optional, default k is 2.

Returned Value: \mathbf{lm} object M .

9. $M = lme(k)$

Description: The function produces the structure matrix of equivalence for k -valued logic ($k \geq 2$).

Argument(s): k is optional, default k is 2.

Returned Value: \mathbf{lm} object M .

10. $M = lmr(k)$

Description: The function produces the power-reducing matrix for k -valued logic ($k \geq 2$).

Argument(s): k is optional, default k is 2.

Returned Value: \mathbf{lm} object M .

11. $M = lmu(k)$

Description: The function produces the dummy matrix for k -valued logic ($k \geq 2$). The dummy matrix M satisfies the following property

$$MXY = Y, \quad \forall X, Y \in D_k.$$

Argument(s): k is optional, default k is 2.

Returned Value: `lm` object M .

12. $M = lmrand(m, n)$

Description: The function produces an $m \times n$ logical matrix randomly.

Argument(s): Positive integers m and n . n is optional, default n is m .

Returned Value: `lm` object M .

13. $M = lwij(m, n)$

Description: The function produces an $mn \times mn$ swap matrix.

Argument(s): Positive integers m and n . n is optional, default n is m .

Returned Value: `lm` object M .

14. $M = randlm(m, n)$

Description: Alias function of *lmrand*.

More usage on `lm` object please find in the examples in Section 3.

3 Examples

Some examples which illustrate the basic usages are listed below with codes, and more examples could be found in the toolbox.

```

1 % This example is to show how to perform semi-tensor product
2
3 x = [1 2 3 -1];
4 y = [2 1]';
5 r1 = sp(x,y)
6 % r1 = [5, 3]
7
8 x = [2 1];
9 y = [1 2 3 -1]';
10 r2 = sp(x,y)
11 % r2 = [5; 3]
12
13 x = [1 2 1 1;
14      2 3 1 2;
15      3 2 1 0];
16 y = [1 -2;
17      2 -1];
18 r3 = sp(x,y)
19 r4 = spl(x,y)
20 % r3 = r4 = [3,4,-3,-5;4,7,-5,-8;5,2,-7,-4]
21
22 r5 = sp(sp(x,y),y)
23 r6 = spn(x,y,y)
24 % r5 = r6 = [-3,-6,-3,-3;-6,-9,-3,-6;-9,-6,-3,0]
```

```

1 % This example is to show the usage of stp class.
2 % Many useful methods are overloaded for stp class , thus you can use stp object as
   double.
3
4 x = [1 2 1 1;
5       2 3 1 2;
6       3 2 1 0];
7 y = [1 -2;
8       2 -1];
9
10 % Covert x and y to stp class
11 a = stp(x);
12 b = stp(y);
13
14 % mtimes method is overloaded by semi-tensor product for stp class
15 c0 = spn(x,y,y)
16 c = a*b*b, class(c)
17
18 % Convert an stp object to double
19 c1 = double(c), class(c1)
20
21 % size method for stp class
22 size(c)
23
24 % length method for stp class
25 length(c)
26
27 % subsref method for stp class
28 c(1,:)
29
30 % subsasgn method for stp class
31 c(1,1) = 3

```

```

1 % This example is to show the usage of lm class.
2 % Many methods are overloaded for lm class.
3
4 % Consider classical (2-valued) logic here
5 k = 2;
6
7 T = lm(1,k); % True
8 F = lm(k,k); % False
9
10 % Given a logical matrix, and convert it to lm class
11 A = [1 0 0 0;
12       0 1 1 1]
13 M = lm(A)
14 % or we can use
15 % M = lm([1 2 2 2], 2)
16
17 % Use m-function to perform semi-tensor product for logical matrices
18 r1 = lspn(M,T,F)
19
20 % Use overloaded mtimes method for lm class to perform semi-tensor product
21 r2 = M*T*F
22
23 % Create an 4-by-4 logical matrix randomly
24 M1 = lmrand(4)
25 % M1 = randlm(4)
26

```



```

27 % Convert an lm object to double
28 double(M1)
29
30 % size method for lm class
31 size(M1)
32
33 % diag method for lm class
34 diag(M1)
35
36 % Identity matrix is a special type of logical matrix
37 I3 = leye(3)
38
39 % plus method is overloaded by Kronecher product for lm class
40 r3 = M1 + I3
41 % Alternative way to perform Kronecher product of two logical matrices
42 r4 = kron(M1, I3)
43
44 % Create an lm object by assignment
45 M2 = lm;
46 M2.n = 2;
47 M2.v = [1 1 2 2];
48 M2

```

```

1 % This example is to show how to use vector form of logic to solve the following
  question:
2 % A said B is a liar , B said C is a liar , and C said A and B are both liars. Who is
  the liar?
3
4 % Set A: A is honest , B: B is honest , C: C is honest
5
6 k = 2;          % Two-valued logic
7 MC = lmc(k); % structure matrix for conjunction
8 ME = lme(k); % structure matrix for equivalence
9 MN = lmn(k); % structure matrix for negation
10 MR = lmr(k); % power-reducing matrix
11
12 % The logical expression can be written as
13 logic_expr = '(A!=B)&(B!=C)&(C=(!A&!B))';
14 % where = is equivalence , & is conjunction , and ! is negation
15
16 % convert the logic expression to its matrix form
17 matrix_expr = lmparser(logic_expr);
18
19 % then obtain its canonical matrix form
20 expr = stdform(matrix_expr);
21
22 % calculate the structure matrix
23 L = eval(expr)
24
25 % The unique solution for  $L \cdot x = [1 \ 0]^T$  is  $x = [0 \ 0 \ 0 \ 0 \ 0 \ 1 \ 0 \ 0]^T = 8[6]$ 
26 sol = v2s(lm(6,8))
27
28 % One can see sol=[0 1 0], which means only B is honest , A and C are liars.

```

```

1 % Examples for Boolean network
2
3 % Initializing
4 k = 2;

```

```

5 options = [];
6
7 % Please note that in this toolbox any variable intialized with capital M is defined
  as a logical matrix, otherwise it will be considered as logical vector.
8 % The followings are some commonly used logical matrices
9 ME = lme(k); % equivalence
10 MI = lmi(k); % implicaiton
11 MD = lmd(k); % disjunction
12 MN = lmn(k); % negation
13 MR = lmr(k); % power-reducing matrix
14 MC = lmc(k); % conjunction
15 MX = lm([2 1 1 2], 2); % xor
16
17 % choose a number from 1-5 to select a Boolean network
18 n = 3;
19
20 switch n
21     case 1
22         % Dynamics of Boolean network
23         %  $A(t+1) = MC*B(t)*C(t)$ 
24         %  $B(t+1) = MN*A(t)$ 
25         %  $C(t+1) = MD*B(t)*C(t)$ 
26         % Set  $X(t)=A(t)B(t)C(t)$ , then
27         eqn = 'MC B C MN A MD B C';
28     case 2
29         % Dynamics of Boolean network
30         %  $A(t+1) = MC*B(t)*C(t)$ 
31         %  $B(t+1) = MN*A(t)$ 
32         %  $C(t+1) = B(t)$ 
33         eqn = 'MC B C MN A B';
34     case 3
35         % Dynamics of Boolean network
36         %  $E(t+1) = MX*E(t)*I(t)$ 
37         %  $H(t+1) = MX*F(t)*H(t)$ 
38         %  $F(t+1) = MX*F(t)*J(t)$ 
39         %  $I(t+1) = MX*G(t)*I(t)$ 
40         %  $G(t+1) = MX*G(t)*MX*F(t)*H(t)$ 
41         %  $J(t+1) = MX*MX*E(t)*I(t)*J(t)$ 
42         % Set  $X(t)=E(t)H(t)F(t)I(t)G(t)J(t)$ , then
43         if k ≠ 2
44             error('This example is only for the case k=2. ');
45         end
46         eqn = 'MX E I MX F H MX F J MX G I MX G MX F H MX MX E I J';
47         % set the variables' order, otherwise they will be sorted in the dictionary
          order
48         options = lmset('vars',{ 'E','H','F','I','G','J'});
49     case 4
50         % Dynamics of Boolean network
51         %  $A(t+1) = MN*MI*K(t)*H(t)$ 
52         %  $B(t+1) = MN*MI*A(t)*C(t)$ 
53         %  $C(t+1) = MI*D(t)*I(t)$ 
54         %  $D(t+1) = MC*J(t)*K(t)$ 
55         %  $E(t+1) = MI*C(t)*F(t)$ 
56         %  $F(t+1) = MN*MI*E(t)*G(t)$ 
57         %  $G(t+1) = MN*MC*B(t)*E(t)$ 
58         %  $H(t+1) = MN*MI*F(t)*G(t)$ 
59         %  $I(t+1) = MN*MI*H(t)*I(t)$ 
60         %  $J(t+1) = J(t)$ 
61         %  $K(t+1) = K(t)$ 
62         % Set  $X(t)=A(t)B(t)C(t)D(t)E(t)F(t)G(t)H(t)I(t)J(t)K(t)$ , then

```

```

63     eqn = 'MN MI K H MN MI A C MI D I MC J K MI C F MN MI E G MN MC B E MN MI F G
           MN MI H I J K';
64     case 5
65         % Dynamics of Boolean network
66         % A(t+1) = MN*MD*C(t)*F(t)
67         % B(t+1) = A(t)
68         % C(t+1) = B(t)
69         % D(t+1) = MC*MC*MN*I(t)*MN*C(t)*MN*F(t)
70         % E(t+1) = D(t)
71         % F(t+1) = E(t)
72         % G(t+1) = MN*MD*F(t)*I(t)
73         % H(t+1) = G(t)
74         % I(t+1) = H(t)
75         % Set X(t)=A(t)B(t)C(t)D(t)E(t)F(t)G(t)H(t)I(t), then
76         eqn = 'MN MD C F A B MC MC MN I MN C MN F D E MN MD F I G H';
77     otherwise
78         return
79 end
80
81 % Convert the equation to a canonical form
82 [expr, vars] = stdform(eqn, options, k);
83
84 % Calculate the network transition matrix
85 L = eval(expr)
86
87 % Analyze the dynamics of the Boolean network
88 [n, l, c, r0, T] = bn(L, k);
89
90 fprintf('Number of attractors: %d\n\n', n);
91 fprintf('Lengths of attractors:\n');
92 disp(l);
93 fprintf('\nAll attractors are displayed as follows:\n\n');
94 for i=1:length(c)
95     fprintf('No. %d (length %d)\n\n', i, l(i));
96     disp(c{i});
97 end
98 fprintf('Transient time: [r0, T] = [%d %d]\n\n', r0, T);

```

References

- [1] D. Cheng, *Matrix and Polynomial Approach to Dynamics Control Systems*, Beijing: Science Press, 2002.
- [2] D. Cheng, H. Qi, *Semi-tensor Product of Matrices — Theory and Applications*, Beijing: Science Press, 2007. (Second Edition, 2011, Both in Chinese)
- [3] D. Cheng, Sime-tensor product of matrices and its applications — A survey, *Proc. ICCM 2007*, Higher Education Press, Hangzhou, 641-668, 2007.
- [4] D. Cheng, H. Qi, Z.Q. Li, *Analysis and Control of Boolean Networks: A Semi-tensor Product Approach*, London: Springer, 2011.
- [5] D. Cheng, H. Qi, Y. Zhao, *An Introduction to Semi-tensor Product of Matrices and Its Applications*, Singapore: World Scientific, 2012.